## CLEANCUT® FUEL PUMP

LIQUID HEATING FUELS AND RENEWABLE FUELS TO R100 / B100 PRODUCT SHEET









CleanCut PF20322

CleanCut PF20323

CleanCut Two-Stage PF20422

#### **Product Description**

The Beckett family of CleanCut® pumps was developed to combine the benefits of solenoid valve control of fuel to the nozzle and the superior lift capabilities of traditional American pumps. The CleanCut pump has established a reputation as a rugged and reliable component for modern heating systems. Now approved for fuels up to 100% biodiesel (B100) the CleanCut pump continues to set the standard of the industry. The Beckett p/n PF20422 is a two-stage version with increased lift ability for applications where the burner is higher than the fuel supply tank. Note: A GeniSys control with prepurge programmed or a Beckett PD Timer® will be needed for proper burner operation.

Beckett offers a complete line of fuel units to meet any application to 35 gph firing rate. Please refer to the table on the reverse side of this sheet for all models offered.

#### **Features**

- Cleaner Operation The valve operation cuts oil flow almost instantly
  when power is cut to the solenoid coil, eliminating coasting stops that
  can cause soot formation on shut-down. The Beckett GeniSys controls
  or Beckett's PD timer work well with the CleanCut pump to bring the
  burner up to full speed before light-off. See illustration below.
- More Reliable There are fewer moving parts compared to conventional pumps and fewer troublesome oil fittings to cause problems. In addition, all of the moving parts in the CleanCut pumps have been in use for years in both the US and in Europe.
- Higher Capacity The unique design of the Cleancut pumps deliver up to 4 gallons per hour at 100 psi. (Note that applications above 3 gph will require an additional valve to meet UL requirements.)
- Reduced Load on Motor Reduces load on the motor during start-up.

# Shut-Off Valve Comparison With Valve - 30 Seconds Cut-Off + 30 Seconds Without Valve - 30 Seconds Cut-Off + 30 Seconds

#### **Pump Model Numbers**

| Beckett Part No. | Manufacturer Part No. | Description               |
|------------------|-----------------------|---------------------------|
| PF20322          | A2EA-6527B            | Single-Stage 4 GPH 120VAC |
| PF20323          | 071N1121              | Single-Stage 4 GPH 120VAC |
| PF20422          | B2EA-6550B            | Two-Stage 4 GPH 120VAC    |

120VAC pumps listed. For other voltage options, please refer to the back of this sheet or visit **www.beckettcorp.com** for more information.

#### **PD Timer**

No control change necessary! If the burner does not have a control the supports valve-on-delay (pre purge), Beckett's PD Timer can be used to add this function without changing the control.



#### **Specifications**

| Nozzle Pressure<br>Range  | 100-200 PSI   |
|---------------------------|---|
| Factory Set<br>Pressure   | 100 PSI   |
| Capacity                  | 4 GPH @ 100-150 PSI (#1 & #2 Fuel Oil)<br>3 GPH @ 150-200 PSI (#2 Fuel Oil)   |
| Operating Fluids          | #1 & #2 Fuel Oils Meeting ASTM D396 with<br>Biodiesel blends up to 100% (B100). ASTM D975<br>with Renewable Diesel Blends to R100.* |
| Inlet/Return<br>Pressures | 10 PSI**  |
| Suction Height            | One Pipe Supply: 6' Max.<br>Two Pipe Supply: 12' Max. (PF20322 / PF20323)<br>Two Pipe Supply: 17' Max. (Two-Stage PF20422)          |
| Rated Speed               | 3450 RPM Nominal  |
| Ambient temp.             | 32°F Min. / 140°F Max.  |
| Electrical<br>Ratings     | 120 VAC (102V Min 132V Max.) 9W Max.<br>220 / 240 VAC (187V Min. – 264V Max.) 9W Max.<br>12VDC (10.2V Min. – 16V Max.) 9W Max.      |
| Certification             | UL, CUL   |
|                           |   |

<sup>\*</sup> For more information on approved fuels for Beckett burners, please refer to Form 664860.

<sup>\*\*</sup>System inlet / return pressures must conform to NFPA 31 (3 PSI) as well as any additional Federal, State, or Local codes.

### **Beckett Pumps for Residential & Commercial Burners**

In addition to our popular CleanCut® pumps, Beckett offers a wide variety of B100 rated fuel pumps as OEM standard new, not remanufactured, replacement pumps and parts. Let Beckett be the source for all your pump replacement and service needs.

- · Capacities from 3 GPH to 35 GPH
- · 2-stage Models
- · 2-step Firing Models
- · 24V / 120V / 240V AC Solenoid Coil Voltages
- · 12V / 24V DC Solenoid Coil Voltages

Replacement Parts and Accessories

Additional pump models and replacement parts listed on the tables below:

#### **Replacement Pumps**

| RWB Part No. | Description                                 | Previous RWB Part No. | Suntec Part No. | Danfoss Part No. | Where Used / Notes              |
|--------------|---|-----------------------|-----------------|------------------|---------------------------------|
| PF20321U     | 1 Stage - 3GPH - 120VAC CleanCut - B100     | PF10321U              | A2EA-6527B      | 071N1121         | 1 stage 'Universal' Replacement |
| PF20322U     | 1 Stage - 3GPH - 120VAC CleanCut - B100     | PF10322U              | A2EA-6527B      |                  |                                 |
| PF20323U     | 1 Stage - 3GPH - 120VAC CleanCut - B100     | PF10323U              |                 | 071N1121         |                                 |
| PF20422U     | 2 Stage - 3GPH - 120VAC Cleancut - B100     | PF10422U              | B2EA-6550B      |                  | 2 Stage                         |
| PF203N2U     | 1 Stage - 3GPH - B100                       | PF103N2U              | A2VA-7116B      |                  | No Solenoid Valve               |
| PF20332U     | 1 Stage - 3GPH - 220VAC CleanCut - B100     | PF10332U              | A2EA-6527B      |                  |                                 |
| PF20333U     | 1 Stage - 3GPH - 220VAC CleanCut - B100     | PF10333U              |                 | 071N1123         |                                 |
| PF20342U     | 1 Stage - 3GPH - 24VDC CleanCut - B100      | PF10342U              | A2EA-6527B      |                  |                                 |
| PF20372U     | 1 Stage - 3GPH - 12VDC/24VAC CleanCut B100  | PF10372U              | A2EA-6527B      |                  |                                 |
| PF20363U     | 1 Stage - 3GPH 12VDC CleanCut - B100        | PF10363U              |                 | 017N1122         |                                 |
| PF205N2U     | 1 Stage - 3GPH - 1725RPM - B100             | PF105N2U              | A1YA-7912B      |                  | No Solenoid Valve               |
| PF206N2U     | 2 Stage - 16GPH - 3450RPM 1/Step - B100     | PF106N2U              | B2TA-8245B      |                  | No Solenoid Valve               |
| PF207N2U     | 2 Stage - 7GPH - B100                       | PF107N2U              | B2YA-8916B      |                  | No Solenoid Valve               |
| PF209N2U     | 1 Stage - 2.5GPH - 2850RPM - B100           | PF109N2U              | A2VA-7142B      |                  | No Solenoid Valve               |
| PF22122U     | 2 Stage - 16GPH - 120VAC - 2/Step - B100    | PF12122U              | B2TA-8851B      |                  |                                 |
| PF22132U     | 2 Stage - 16GPH - 220VAC - 2/Step - B100    | PF12132U              | B2TA-8851B      |                  |                                 |
| PF22322BRU   | 2 Stage - 23GPH - 120VAC - 2/Step w/BAR Kit | PF12322BRU            | B2TA-8851B      |                  |                                 |
| PF22322U     | 2 Stage - 23GPH - 120VAC - 2/Step - B100    | PF12322U              | B2TA-8852B      |                  |                                 |
| PF224N2BRU   | 2 Stage - 8GPH - w/BAR Kit                  | PF124N2BRU            | B2TA-8248B      |                  |                                 |
| PF224N2U     | 2 Stage - 8GPH - B100                       | PF124N2U              | B2TA-8248B      |                  | No Solenoid Valve               |
| PF226N2U     | 1 Stage - 7GPH - B100                       | PF126N2U              | A2YA-7916B      |                  | No Solenoid Valve               |
| PF245N2U     | 35GPH - 3450 / 1725                         | PF145N2U              | J4PAC10038M     |                  |                                 |
| PF812N2U     | 1 Stage - 2.5GPH - 3450/1725 Waste Oil      | 21219U                | A2RA-7736       |                  | Waste Oil Burner Applications   |

#### **Pump Parts and Accessories**

| RWB Part No. | Description                                     | Previous RWB Part No. | Suntec Part No. | Danfoss Part No. | Where Used / Notes              |
|--------------|---|-----------------------|-----------------|------------------|---------------------------------|
| 21807U       | Cordset - 13" Non-Delay                         |                       |                 |                  | All CleanCut® Pumps             |
| 21887U       | Cordset - 13" w/ PD Timer                       |                       |                 |                  | All CC Pumps - 4 Sec time Delay |
| 52585U       | CleanCut Pump Instructions & By-Pass Plugs      |                       |                 |                  | All CleanCut Pumps              |
| 3713824U     | Solenoid Coil 120VAC                            | 21755U                | 3713824         |                  | PFx0322                         |
| 3713798U     | Solenoid Coil 240VAC                            | 21756U                | 3713798         |                  | PFx0332                         |
| 3713823U     | Solenoid Coil 12VDC / 24VAC                     | 21754U                | 3713823         |                  | PFx0372                         |
| 071N0805U    | Solenoid Coil 120VAC                            |                       |                 | 071N0805         | PFx0323                         |
| 071N0806U    | Solenoid Coil 240VAC                            |                       |                 | 071N0806         | PFx0333                         |
| 071N0807U    | Solenoid Coil 12VC                              |                       |                 | 071N0807         | PFx0363                         |
| 21877U       | Valve Stem                                      |                       |                 |                  | All PFx03x2 Pumps               |
| S160-14      | Cleancut Strainer Kit with Bio gasket           | SP105281U             |                 |                  | All 1-stage CleanCut Pumps      |
| S197         | Danfoss BFPH Strainer Kit                       | SP150223U             |                 |                  | Danfoss Model BFPH Only         |
| S170-1       | Suntec 2-Step Pumps - 16/23GPH                  | SP250402U             |                 |                  | Suntec B2TA-8851 / 8852         |
| S190-8-10    | Strainer Cover Gasket (10) - Bio gasket to B100 | SPG33172BU            |                 |                  | PFx03x2 Pumps                   |
| S190-7-10    | Strainer Cover Gasket (10) - Cork (up to B5)    | SPG33112BU            |                 |                  | PF1xxx Pumps                    |
| S197-5-10    | Strainer Cover O-Ring (10) - Viton to B100      | SPG33129BU            |                 |                  | PFx03x3 Pumps                   |

#### www.beckettcorp.com

USA: R.W. Beckett Corporation, 1-800-645-2876 Canada: R.W. Beckett Canada Ltd, 1-800-665-6972

Printed in the USA 02/23

Part No. 61408 R05

This document and all information contained herein are the sole property of the R.W. Beckett Corporation and cannot be reproduced or transmitted in whole or part without express written permission of the R.W. Beckett Corporation.

