

Job Name: _____

Purchaser: _____

Submitted To: _____

Construction: _____

Reference: _____

Approval: _____

Date: _____

Submitted By: _____

Unit: _____

Drawing #: _____

QS12WP2BEA



Indoor Accessories


Remote Controller (Included)	WJ26X35394
Wired Controller	QACT17B
Refrigerant Detection Sensor (RDS)	UALS01A

Specifications

Cooling	Rated Cooling Capacity Btu/hr	12,000
Heating	Rated Heating Capacity Btu/hr	13,000
Power	Voltage, Cycle, Phase V/Hz/Phase	208-230/60/1
	Operating Voltage Range	187-253 VAC
Indoor Unit	Fan Speed Stages	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	410/370/280/210/170
	Motor Speed RPM: Cooling (Turbo/High/Med/Low/Quiet)	1300/1250/1050/850/610
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	46/44/38/32/25
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	420/390/350/310/180
	Motor Speed RPM: Heating (Turbo/High/Med/Low/Quiet)	1300/1250/1150/1050/610
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/42/39/36/25
	Auto Up-Down Louver	Yes
	Auto Left-Right Louver	Yes
	Dimension: H x W x D in (mm)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)
	Weight (Net/Ship)- lbs (kg)	24.49/30.56 (11.1/13.85)
	Drain Pipe Size O.D in	5/8
	WiFi*	Built-in
Refrigerant Line	Factory-Installed Refrigerant Detection Sensor (RDS)	No
	Refrigerant Detection Sensor (RDS) Compatible	Yes
	Liquid O.D. in	1/4
	Suction O.D. in	3/8

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

QS12WP2BEA



Note: Dimensions are shown in inches (millimeters)

SUBMITTAL REVISION HISTORY

03-31-25: Submittal release.