



Haier

POWERED BY
SmartHQ™



Single Zone Ductless Heat Pump Systems




GE APPLIANCES
a Haier company


AIR&WATER
SOLUTIONS

Single Zone Solutions

Haier



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.




-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with 100% heating capacity at 5°F.



WARM START & AUTO START

Warm start ensures the fan does not blow cold air during heating mode startup. Auto restart automatically restarts the system after a power outage for seamless operation.




MOUNTING TEMPLATE/PLATE

A convenient printed cardboard template and mounting plate enable accurate, single-person installation, ensuring correct positioning of the lineset and drain opening.



EXTENDED KICKSTAND

The built-in bracket provides extra room for easier installation and service.



2-WAY PIPING DRAIN

Flexible right or left side condensation drain options simplify installation (right side only with RDS installed).



EASY-ACCESS PCB

The PCB pops out for quick component and wiring checks, eliminating the need to remove the casing.



TURBO MODE


Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



INDOOR AIR FILTER

The easily removable and cleanable indoor air filter reduces maintenance time, ensuring cleaner air and longer-lasting efficiency.

ADDITIONAL PREMIUM HIGHWALL FEATURES



3-D AIRFLOW

Designed to oscillate up and down, left and right automatically, ensuring optimal distribution of conditioned air throughout the space.



SMART SENSOR

Automatically changes to an energy-saving temperature while you are away, then back to your regular setting when you return.



FOLLOW & SURROUND

Allows the user to choose if the air is directed towards them (follow) or away from them (surround).

Note: Features vary by individual models.



Premium Highwall Specifications



	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	QS09WP2BEA	QS12WP2BEA	QS18WP2BEA
Cooling	Rated Capacity Btu/hr	9,000	12,000	17,000
	Capacity Range Btu/hr	3,200-10,000	4,200-13,000	6,000-18,500
	SEER2	27	25	20.5
	EER2	12.5	12.5	12
	Moisture Removal Pt./hr	2.30	3.80	4.80
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	14,500	19,000
	Heating Capacity Range Btu/hr	3,600-12,000	3,600-15,500	5,600-21,000
	HSPF2 (IV)	11.0	11.0	10.0
	Rated Heating Capacity 5°F Btu/hr	10,000	14,500	19,000
	Heating Capacity at 5°F / Capacity at 47°F	100%	100%	100%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Fuse Size A	20	20	30
	Minimum Circuit Amp A	13	14	20
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	395/355/310/260/170	410/370/280/210/170	580/530/480/400/350
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	395/355/290/220/170	420/390/350/310/180	580/530/450/350/320
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/42/36/32/27	46/44/38/32/25	51/50/44/37/25
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/41/37/32/29	43/42/39/36/25	49/47/40/35/26
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	Yes	Yes	Yes
	Drain Pipe Size O.D in	5/8	5/8	5/8
	Dimension: H x W x D in (mm)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 1/4 x 36 x 8 3/8 (312 x 914 x 213)	12 7/8 x 39 3/4 x 8 3/4 (327 x 1009 x 223)
	Weight (Net/Ship) - lbs (kg)	24.49/30.56 (11.1/13.85)	24.49/30.56 (11.1/13.85)	29.57/36.63 (13.4/16.6)
	Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No
	Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
	WiFi*	Built-in	Built-in	Built-in
Refrigerant Lines	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15


*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.



GE APPLIANCES
a Haier company

AIR & WATER
SOLUTIONS

www.GEAppliancesAirAndWater.com



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.




-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.



COMPACT DESIGN

Fits 2' x 2' drop ceiling for easy installation.



CONDENSATE PUMP

Factory-installed condensate pump.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.




INDEPENDENT LOUVER CONTROL

The four cassette louvers can be set to the same, or different positions, to control airflow direction.

Note: Features vary by individual models.



Compact Cassette Specifications



	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	US09CB2BEA	US12CB2BEA	US18CB2BEA
	Panel (required, sold separately)	QACCP01WA	QACCP01WA	QACCP01WA
Cooling	Rated Capacity Btu/hr	9,000	12,000	18,000
	Capacity Range Btu/hr	3,000-10,000	3,000-13,000	6,000-19,000
	SEER2	20	20	20
	EER2	12	12	12
	Moisture Removal Pt./hr	2.40	3.50	5.50
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	12,500	18,000
	Heating Capacity Range Btu/hr	3,000-11,000	3,000-14,000	6,000-19,500
	HSPF2 (IV)	10.0	10.0	10.0
	Rated Heating Capacity 5°F Btu/hr	9,000	10,000	14,400
	Heating Capacity at 5°F / Capacity at 47°F	90%	80%	80%
Operating Range	COP 5°F	1.8	1.8	1.8
	Cooling (Without Wind Baffle or Top Cover)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)
Power Supply	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Fuse Size A	20	20	30
Outdoor Unit	Minimum Circuit Amp A	13	14	20
	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
Indoor Unit	Basepan Heater	Yes	Yes	Yes
	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	458/425/387/345/302
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	440/387/351/320/290	440/387/351/320/290	479/441/387/345/302
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	42/40/36/32/25	45/42/40/36/32	45/42/40/36/32
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	No	No	No
	Dimension: H x W x D in (mm)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)	10 1/4 x 22 3/4 x 22 3/4 (260 x 575 x 575)
	Weight (Net/Ship) - lbs (kg)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)	32.41/47.4 (14.7/21.5)
	Drain Pipe Size O.D in	1*	1*	1*
	Condensate Pump	Built-In	Built-In	Built-In
	Max. Drain-Lift Height in (mm)	47 1/4 (1200)	47 1/4 (1200)	47 1/4 (1200)
	Factory-Installed Refrigerant Detection Sensor (RDS)	No	No	No
	Refrigerant Detection Sensor (RDS) Compatible	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)	Yes (UALS01A, sold separately)
Refrigerant Lines	WiFi**	Built-in	Built-in	Built-in
	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.


**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.

Single Zone Solutions

Haier



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.



-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.



WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



AIRFLOW DIRECTION CONTROL

Allows the homeowner to select preferred airflow direction - the top and bottom or top only.



INSTALLATION FLEXIBILITY

Unit can be placed on the floor or installed low on the wall.




ROOM TEMPERATURE DISPLAY

Easy-to-read dual seven segment display on the front of the panel.

Note: Features vary by individual models.



Console Specifications



	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	US09FB2BEA	US12FB2BEA	US18FB2BEA
Cooling	Rated Capacity Btu/hr	9,000	12,000	17,000
	Capacity Range Btu/hr	3,000-10,000	3,000-13,500	6,000-18,500
	SEER2	20	20	19
	EER2	12	12	9
	Moisture Removal Pt./hr	2.16	3.40	3.80
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	12,300	18,000
	Heating Capacity Range Btu/hr	2,500-10,000	2,500-13,000	6,000-19,000
	HSPF2 (IV)	10.5	9.5	9.5
	Rated Heating Capacity 5°F Btu/hr	9,000	10,000	14,400
	Heating Capacity at 5°F / Capacity at 47°F	90%	81%	80%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Fuse Size A	20	20	30
	Minimum Circuit Amp A	13	14	20
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	290/218/205/176/147	314/226/210/195/175	345/341/271/218/210
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	312/206/205/176/147	311/223/200/195/175	345/300/280/218/210
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/40/37/32/24	47/41/37/33/25	49/44/43/40/37
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	43/37/32/27/20	47/40/37/33/25	49/43/43/37/37
	Auto Up-Down Louver	Yes	Yes	Yes
	Auto Left-Right Louver	No	No	No
	Drain Pipe Size O.D in	5/8	5/8	5/8
	Dimension: H x W x D in (mm)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)	23 5/8 x 27 1/2 x 8 3/4 (600 x 700 x 220)
	Weight (Net/Ship) - lbs (kg)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)	32.41/43.43 (14.7/19.7)
	Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes
	WiFi*	Built-in	Built-in	Built-in
	Refrigerant	R454B	R454B	R454B
Refrigerant Lines	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15

*WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.



GE APPLIANCES
a Haier company

AIR & WATER
SOLUTIONS


www.GEAppliancesAirAndWater.com

Single Zone Solutions

Haier



OPERATING RANGE (°F):



R454B REFRIGERANT

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



OVER-THE-AIR UPDATES

A high-speed communication wire between the outdoor and indoor unit allows outdoor unit over-the-air (OTA) updates via the SmartHQ™ Home app.



DC INVERTER TECHNOLOGY

Advanced DC inverter technology enhances energy efficiency, cuts costs, and improves reliability, making it ideal for energy-conscious homeowners.



BLUE FIN

A hydrophilic aluminum fin provides corrosion protection and ensures smooth water flow for long-lasting performance.



BASEPAN HEATER

A basepan heater prevents ice buildup and condensate water accumulation in the outdoor unit, ensuring smooth operation.



-31°F HEATING

Reliable low ambient heating down to -31°F ensures comfort and efficiency even in extreme conditions with 100% heating capacity at 5°F.



AUTO RESTART

Automatically restarts the system after a power outage for seamless operation without manual intervention.




WARM START

Ensures the fan does not blow cold air during heating mode startup.



TURBO MODE

Delivers rapid cooling or heating, making it ideal for quickly adjusting the room temperature.



COMPACT DESIGN

Less than 10" height saves ceiling space.



CONDENSATE PUMP

Factory-installed condensate pump.



0.6" EXTERNAL STATIC

Designed for static pressure up to 0.6" w.g.



FRESH AIR KNOCKOUT

Unit designed with a 4" round fresh air knockout.



AUXILIARY HEATER COMPATIBLE

Compatible with many third-party auxiliary heaters.



OPTIONAL ACCESSORIES

MERV filter box and supply plenums available (sold separately) for easy installation.

Note: Features vary by individual models.



Mid-Static Ducted Specifications



	Outdoor Unit	1Q09RT2BEA	1Q12RT2BEA	1Q18RT2BEA
	Indoor Unit	US09MB2BEA	US12MB2BEA	US18MB2BEA
Cooling	Rated Capacity Btu/hr	9,000	10,000	18,000
	Capacity Range Btu/hr	3,000-10,000	3,000-11,000	6,000-19,000
	SEER2	19.6	19.8	18
	EER2	12	11.7	11.7
	Moisture Removal Pt./hr	1.10	1.18	3.80
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	14,000	20,000
	Heating Capacity Range Btu/hr	3,000-12,500	3,000-14,500	6,000-20,500
	HSPF2 (IV)	10.5	10.5	10.5
	Rated Heating Capacity 5°F Btu/hr	8,000	10,000	17,000
	Heating Capacity at 5°F / Capacity at 47°F	80%	71%	85%
	COP 5°F	1.8	1.8	1.8
Operating Range	Cooling (Without Wind Baffle or Top Cover)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)	23°F~115°F (-5~46°C)
	Heating	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)	-31~75°F (-35~24°C)
Power Supply	Voltage, Cycle, Phase (V/Hz/-)	208-230/60/1	208-230/60/1	208-230/60/1
	Maximum Fuse Size A	20	20	30
	Minimum Circuit Amp A	13	14	20
Outdoor Unit	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Outdoor Noise Level dB	54	55	60
	Dimension: H x W x D in (mm)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	25 1/4 x 35 3/8 x 12 (642 x 898 x 306)	27 3/4 x 38 3/8 x 13 3/8 (705 x 974 x 340)
	Weight (Net/Ship) - lbs (kg)	83.41/96.87 (37.8/43.9)	88.15/100.4 (39.95/45.5)	104.59/122.46 (47.4/55.5)
	Basepan Heater	Yes	Yes	Yes
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
	Airflow CFM: Cooling (Turbo/High/Med/Low/Quiet)	353/286/200/150/141	409/350/308/158/148	620/517/332/214/203
	Airflow CFM: Heating (Turbo/High/Med/Low/Quiet)	358/292/208/155/145	412/355/311/163/152	627/523/337/217/205
	Indoor Sound Level dB: Cooling (Turbo/High/Med/Low/Quiet)	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36
	Indoor Sound Level dB: Heating (Turbo/High/Med/Low/Quiet)	44/41/38/35/32	47/44/41/38/35	48/45/42/39/36
	Dimension: H x W x D in (mm)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 31 3/4 x 27 1/2 (248 x 805 x 700)	9 3/4 x 47 1/2 x 27 1/2 (248 x 1207 x 700)
	Weight (Net/Ship) - lbs (kg)	62.17/86.86 (28.2/39.4)	62.17/86.86 (28.2/39.4)	87.74/123.46 (39.8/56)
	Drain Pipe Size O.D in	1*	1*	1*
	Max. External Static Pressure in.W.G (Pa)	0.6 (150)	0.6 (150)	0.6 (150)
	Condensate Pump	Built-in	Built-in	Built-in
	Max. Drain-lift height in (mm)	27 1/2 (700)	27 1/2 (700)	27 1/2 (700)
	Factory-Installed Refrigerant Detection Sensor (RDS)	Yes	Yes	Yes
	WiFi**	Built-in	Built-in	Built-in
	Refrigerant	R454B	R454B	R454B
	Connections	Flare	Flare	Flare
Refrigerant Lines	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	46.6	50.1	58.6
	Maximum Line Length Ft / m	66/20	66/20	83/25
	Maximum Height Ft / m	33/10	33/10	50/15

*Condensate drain adapter shipped with the indoor unit is designed to accept a 3/4" PVC pipe.

**WiFi includes SmartHQ™ Home and SmartHQ™ Service compatibility.



Haier



LIMITED WARRANTY

We take pride in our workmanship; our standard coverage includes a 5-year limited warranty on parts.

Additionally, our ductless systems qualify for a 10-year limited warranty on parts with registration. To receive the extended coverage, equipment must be registered within 60 days of installation. Please refer to the warranty documentation for complete details.



To register your equipment go to:
www.geappliancesairandwater.com/warranty



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

